



Symbol LS7708



FEATURES

Rastering scan pattern

Speeds customers through checkout by maximizing first-pass read rates and reads truncated bar codes

RSS bar code decoding

Supports new, RSS bar codes to future proof your investment

Multi-interface capability

Protects your investment by allowing migration to future hosts with only a cable change

Universal cables

Saves money with one cable used across the Motorola product line

Scan stitching

Improves first-pass read rate and increases productivity

Enhance customer service with faster checkouts

Moving customers through checkout quickly is one of the most important issues faced by retailers today. The Symbol LS7708 horizontal presentation scanner from Motorola is the perfect choice for retailers looking for higher throughput and increased productivity.

The on-counter Symbol LS7708 is available for presentation or swipe scanning in an attractive form factor. For fast, accurate merchandise scanning at checkout, this easy-to-use, hands-free scanner requires minimal operator effort. Every feature contributes to increased performance for more efficient, rapid customer checkouts.

Superior design and flexibility

The Symbol LS7708's easy-to-use design enables employees to spend more time with customers. It has a large scan window for easy and intuitive scanning. An omni-directional, rastering scan pattern with moving laser scan lines delivers superior first-pass read rates and better performance on truncated symbols.

For retailers with occasional bulky or heavy items, the Symbol LS7708 features a secondary scanner port to connect a handheld scanner. This removes the need for customers or associates to pick up and place cumbersome items on the counter, which saves valuable time. The Symbol LS7708 combines

the benefits of productive, hands-free scanning with the versatility of a handheld scanner.

High performance at an affordable price

For medium- to high-volume retailers such as drug, grocery, specialty soft goods, hard goods and department stores, the Symbol LS7708 offers a cost-effective, hands-free solution. The Symbol LS7708 is designed for maximum uptime to withstand the toughest and busiest retail environments. An integrated EAS antenna in every scanner provides the interface for electronic article surveillance (EAS) de-activation, which makes the Symbol LS7708 one of the best values on the market today.

Lower Total Cost of Ownership (TCO)

For a lower TCO, the Symbol LS7708 scanner has the identical solid reliability of the successful Symbol LS5700 plus added performance capabilities. Symbol LS7708 scanners read Reduced Space Symbology® (RSS), which offers tracking identification for produce and pharmaceuticals, to future proof your investment.

Increase associate and checkout productivity

First-pass data capture and the elimination of time previously orienting bar codes combines with secondary scanning capabilities to improve worker productivity and point-of-sale throughput. Checkout is faster and more efficient, ultimately improving

SPECIFICATION SHEET

SYMBOL LS7708

Electronic article surveillance (EAS)

Saves time by eliminating the need to de-activate security tag in a separate step

PC programming (123 Scan)

Allows for easy programming and set up of scanners — ideal for large installations

Secondary scanner port

Enables connectivity to secondary scanner for scanning heavy or oversized merchandise

Automatic sleep mode

Reduces power demand and increases life of the scanner

customer satisfaction — and service. And when it comes to implementation, you can count on Motorola for the help you need to get and keep your investment up and running at peak performance. Motorola offers complete training, installation and ongoing support services to provide seamless

deployment, management and continued support of all your advanced data capture solutions.

For more information, visit us on the web at www.motorolasolutions.com/LS7708

Symbol LS7708 Specifications

Physical Characteristics		User Environment	
Dimensions without stand:		Operating Temperature:	32° to 104°F (0° to 40° C)
16 cm H x 5.98 in. W x 3.73 in. D		Storage Temperature:	-40° to 158°F (-40° to 70°C)
Weight:		Humidity:	5% to 95% (non-condensing)
Scanner only: 2 lbs. (907 g)		Ambient Lighting Tolerance:	Tolerant to typical artificial indoor and natural outdoor (direct sunlight) lighting conditions. Fluorescent, Incandescent, Mercury Vapor, Sodium Vapor, LED ¹ : 450 Ft Candles (4,844 Lux) Sunlight: 8000 Ft Candles (86,111 Lux)
Power Source:		EAS Support:	Electronic Article Surveillance Antenna (EAS) Included; Interlock feature for Sensormatic and Checkpoint
Power drawn from Host terminal or external power supply; depends on Host type		Regulatory	
Voltage:		Electrical Safety:	Certified to UL 1950, CSA C22.2 No. 950 EN60825
5.5 VDC to 4.75 VDC measured at host terminal or external power supply		Laser Safety:	CDRH Class IIa Laser Product; IEC 60825 Class 1 Laser Product
Typical/Max Current:		EMC:	CISPR B, FCC B
390mA/500mA		Warranty	
Power Source:		The Symbol LS7708 is warranted against defects in workmanship and materials for a period of 2 years (24 months) from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions. See full warranty for details.	
2 watts		NOTICE: Repairs of this product may require the use of Motorola proprietary parts (and/or Motorola proprietary information). Motorola will sell these parts (and provide this proprietary information) only to end-user customers for self-service. It is Motorola's policy not to sell these parts to third-party service providers and not to allow a third-party service provider to act as an ordering or receiving agent for the parts necessary to repair this product. Applicable in the US. For all other countries, please contact your Motorola account manager or the local Motorola Customer Service representative in your area for further details.	
Mounting Options:		1 - Refers to 100% UPC bar code (80% contrast) located 4 in./10 cm. from the scanner nose.	
Integral Mounting Bracket		2 - LED lighting with high AC ripple content can impact scanning performance	
Color:			
Twilight Black			
Performance Characteristics			
Light Source:			
650 nm visible laser diode			
Print Contrast:			
25% minimum reflective difference			
Scan Patterns:			
Static/Raster - Omni-directional: 24/120 scan lines			
Scan Rate:			
Static/Raster - Omni-directional: 2400 scans/second			
Typical Working Range:			
5 mil: (38%) 0.5 in - 2.5 in (1.25 cm - 6.4 cm)			
7.8 mil: (60%) 0 - 5.0 in (0 -12.7 cm)			
10.4 mil: (80%) 0 - 7.5 in (0 -19.0 cm)			
13 mil: (100%) 0 - 10.0 in (0 - 25.4 cm)			
Depth of Field:			
0-10 in/25 cm @ 13 mil (100% UPC/EAN)			
Minimum Resolution ¹ :			
5 mil			
Decode Capability:			
UPC/EAN/JAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 128, ISBT 128, Code 39, Code 39 Trioptic, Interleaved 2 of 5, Discrete 2 of 5, Code 93, Code 11, Codabar, RSS Variants			
Interfaces Supported:			
USB, RS 232, IBM® 468X/9X, Keyboard Wedge, and Synapse™ (allows connectivity to virtually every POS host type), SPCI (for 123 Scan)			



MOTOROLA

motorola.com

Part number PSS-LS7708-A. Printed in USA 10/12. MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © Motorola Solutions, Inc. 2012. All rights reserved. Specifications are subject to change without notice.